

DSWA ASBESTOS DISPOSAL PROCEDURE
FOR
THE CENTRAL SOLID WASTE MANAGEMENT CENTER
(SANDTOWN LANDFILL)

AND

THE SOUTHERN SOLID WASTE MANAGEMENT CENTER
(JONES CROSSROADS LANDFILL)

TABLE OF CONTENTS

| | |
|--------|--|
| Page 2 | Category I Non-Friable Asbestos (Category I Non-Friable Asbestos Containing Material (ACM) means asbestos-containing packings, gaskets, resilient floor covering, and asphalt roofing products) |
| Page 4 | Category II Non-Friable Asbestos (Category II Non-Friable asphalt/vinyl floor tiles, mastic/adhesive, transite materials and house siding are considered Category II materials) |

DSWA ASBESTOS DISPOSAL PROCEDURE
FOR
CATEGORY I NON-FRIABLE ASBESTOS CONTAINING MATERIAL (ACM)*

This procedure shall become effective April 1, 1995. Category I non-friable ACM will be accepted at the Central Solid Waste Management Center (CSWMC) and the Southern Solid Waste Management Center (SSWMC) provided that the following procedure is followed:

1. The waste must be generated in the State of Delaware.
2. The CSWMC and SSWMC will accept Category I non-friable ACM loads generated and brought by homeowners without limitation on quantity. Category I non-friable ACM brought by an asbestos abatement contractor will be limited to five (5) cubic yards or less. Category I non-friable ACM loads brought by asbestos abatement contractors which are greater than five (5) cubic yards must be taken to the Northern Solid Waste Management Center (NSWMC), Wilmington, DE (302-577-3457 or 302-764-2732).
3. A copy of the Authority's Asbestos Disposal Form/Waste Shipment Record, properly filled out, and the Category I non-friable ACM certificate, must accompany each asbestos load for our records. This is to be delivered to the weighmaster at the scalehouse with each load and verified by the Landfill Asbestos Inspector.
4. The Authority must be contacted at least twenty-four (24) hours prior to delivery to the landfill for an appointment. Notification should be made by calling the CSWMC (Sandtown) at (302) 284-3933 or the SSWMC (Jones Crossroads) at (302) 875-2004. If you cannot make your scheduled appointment, please call immediately and reschedule.
5. Asbestos will be accepted from 8:00 a.m. to 3:00 p.m. Monday through Friday only. Unloading must be completed by 4:00 p.m.
6. All asbestos loads containing Category I non-friable ACM must be wetted and covered.
7. Upon arrival, the customer must notify the weighmaster at the scale that the load is asbestos containing material.
8. Friable or Category II non-friable ACM shall not be mixed with Category I non-friable ACM.
9. Asbestos waste must be unloaded by the customer at a location and in a manner as directed by the Asbestos Inspector.
10. All vehicles carrying asbestos, except for homeowners, must display a placard while loading and unloading asbestos to read as follow:

DANGER
ASBESTOS DUST HAZARD
CANCER AND LUNG DISEASE HAZARD
Authorized Personnel Only

If all the above described procedures are followed, the customer will be charged the current asbestos disposal user fee as established by the DSWA.

* Category I non-friable Asbestos Containing Material (ACM) means asbestos-containing packings, gaskets, resilient floor covering, and asphalt roofing products containing more than one (1) percent asbestos, as determined using the method specified in Appendix A, Subpart F, 40 CFR, part 763, Section 1, Polarized Light Microscopy.

DSWA ASBESTOS DISPOSAL PROCEDURE
FOR
CATEGORY II NON-FRIABLE ASBESTOS CONTAINING MATERIAL (ACM)*

This procedure shall become effective April 1, 1995. Category II non-friable ACM will be accepted at the Central Solid Waste Management Center (CSWMC) and Southern Solid Waste Management Center (SSWMC) provided that the following procedure is followed:

1. The waste must be generated in the State of Delaware.
2. The CSWMC and SSWMC will accept Category II non-friable asbestos loads generated and brought by homeowners without limitation on quantity. Category II non-friable ACM brought by an asbestos contractor will be limited to five (5) cubic yards or less. Category II non-friable ACM loads brought by asbestos abatement contractors, which are greater than five (5) cubic yards, must be taken to the Northern Solid Waste Management Center (NSWMC), Wilmington, DE (302-577-3457 or 302-764-2732).
3. A copy of the Authority's Asbestos Disposal Form/Waste Shipment Record, properly filled out, must accompany each asbestos load for our records. This is to be delivered to the weighmaster at the scalehouse with each load and verified by the Landfill Asbestos Inspector.
4. The Authority must be contacted at least twenty-four (24) hours prior to delivery to the landfill for an appointment. Notification should be made by calling the CSWMC (Sandtown) at (302) 284-3933 or the SSWMC (Jones Crossroads) at (302) 875-2004. If you cannot make your scheduled appointment, please call immediately and reschedule.
5. Asbestos will be accepted from 8:00 a.m. to 3:00 p.m. Monday through Friday only. Unloading must be completed by 4:00 p.m.
6. All asbestos must be wetted and packaged in **leak-proof clear plastic wrap or bags** with a minimum of two (2) independent layers of 6 mil plastic, sealed with duct tape or equivalent waterproof tape, and labeled with the following two messages:

DANGER
CONTAINS ASBESTOS FIBERS
AVOID CREATING DUST
CANCER AND LUNG DISEASE HAZARD

and

Waste Generator's Name and Address

Any other type of container must first receive approval from the DSWA.

The Authority may reject any asbestos waste which, in its sole opinion, is not properly wetted, packaged, or is contained in damaged packaging.

7. Upon arrival, the customer must notify the weighmaster at the scale that the load is asbestos containing material.
8. Friable ACM shall not be mixed with Category II non-friable ACM.
9. Asbestos waste must be unloaded by the customer at a location and in a manner as directed by the Asbestos Inspector.
10. All vehicles carrying asbestos, except for homeowners, must display a placard while loading and unloading asbestos to read as follow:

DANGER
ASBESTOS DUST HAZARD
CANCER AND LUNG DISEASE HAZARD
Authorized Personnel Only

If all the above described procedures are followed, the customer will be charged the current asbestos disposal user fee as established by the DSWA.

* Category II non-friable Asbestos Containing Material (ACM) means any material, excluding Category I non-friable ACM, containing more than one (1) percent asbestos, as determined using the method specified in Appendix A, Subpart F, 40 CFR, part 763, Section 1, Polarized Light Microscopy (PLM) that, when dry, cannot be crumbled, pulverized, or reduced to powder by hand pressure.

NOTE: asphalt/vinyl floor tiles, mastic/adhesive, transite materials and house siding are considered Category II materials.